




TABELL KJETTINGREDSKAP

GRADE 80 (K8) & GRADE 100 (K10)

Sikkerhetsfaktor 4	1 PART				2 PARTER				3-4 PARTER				$\beta = \angle =$ Arbeidsvinkel
	RETT STREKK		SNARET		$\beta \angle$ til 45°		$\beta \angle$ 45° - 60°		$\beta \angle$ til 45°		$\beta \angle$ 45° - 60°		Redskap skal være merket med WLL/SWL, ID-nummer og leverandøridentitet. G80/K8 kjettingredskaper har 8-kantet merkebrikke. Winner G100 har 2 typer kjetting: WIN200 og WIN400. Redskap med G100/WIN200 har 10-kantet brikke. G100/WIN400 har oval brikke. Standard sertifisering av flerpartet redskap: Arbeidsvinkel (β) = 45° OVERSKRID ALDRI TOPPVINKEL 120°
Dim. (mm)	K8	K10	K8	K10	K8	K10	K8	K10	K8	K10	K8	K10	
5	0,80	1,00	0,64	0,80	1,12	1,40	0,80	1,00	1,60	2,00	1,18	1,50	
6	1,12	1,40	0,90	1,12	1,60	2,00	1,12	1,40	2,36	3,00	1,70	2,12	
7	1,50	1,90	1,20	1,50	2,12	2,65	1,50	1,90	3,15	4,00	2,24	2,80	
8	2,00	2,50	1,60	2,00	2,80	3,55	2,00	2,50	4,25	5,30	3,00	3,75	
10	3,15	4,00	2,50	3,15	4,25	5,60	3,15	4,00	6,70	8,00	4,75	6,00	
13	5,30	6,70	4,25	5,30	7,50	9,50	5,30	6,70	11,20	14,00	8,00	10,00	
16	8,00	10,00	6,30	8,00	11,20	14,00	8,00	10,00	17,00	21,20	11,80	15,00	
19	11,20	14,00	8,95	11,20	16,00	20,00	11,20	16,00	23,60	30,00	17,00	21,20	
22	15,00	19,00	12,00	15,00	21,20	26,50	15,00	19,00	31,50	40,00	22,40	28,00	
26	21,20	26,50	16,95	21,20	30,00	37,50	21,20	26,50	45,00	56,00	31,50	40,00	
32	31,50	40,00	25,20	31,50	45,00	56,00	31,50	40,00	67,00	85,00	47,50	60,00	
Faktor	1		0,8		1,4		1		2,1		1,5		

TEMPERATUR (C) G80 & WIN 400			KANTBELASTNING (Ø=diameter)		
-40° til 200°	200°-300°	300-400 (380)			
1	0,9	0,75	R>2Ø	R>Ø	Skarpe kanter
Let: 1	Medium: 0,7	Kraftig: ikke tillatt	1	0,7	0,5

**G100 kan belastes
25 % mer enn G80.**

Winner dominates!

**TOTALLEVERANDØR
GIR TOTALGARANTI!**

Transportutstyr AS

Tlf.nr. +47 63 87 10 80 Faks: +47 63 87 40 30
www.transportutstyr.no post@transportutstyr.no